

SMILE-T10-HV



Model	SMILE-T10-HV
System Specification	
Nominal Output Power	10000 W
Capacity Range	8.2 ~ 49.2 kWh (95% DoD)
Battery Chemistry	LFP (LiFePO4)
IP Protection	IP65 (Outdoor)
Warranty	10 Year Product Warranty, 10 Year Performance Warranty

Inverter Technical Specification			
Model	SMILE-T10-HV-INV	Rated Voltage	380 / 400 V
Max. PV Input Power	16000 W	Phase	Three phase
Max. PV Input Current	2 x 26 A	Backup	UPS
Max. PV Input Voltage	1000 V	Communication	Ethernet / WiFi / 4G
MPPT Number/Max. input strings number per MPPT	2/2	Start Up Voltage	160 V
MPPT Voltage Range	200 ~ 850 V	Humidity	15% ~ 85% (No Condensing)
Max. PV Short-circuit Current	2 x 39 A	Dimension (W x D x H)	580 x 230 x 606 mm
Max. Charging/Discharging Current	40 A	Weight	30 kg
Max. Charging/Discharging Power	10000 W	Safety	IEC 62109, IEC 62040
Rated Frequency	50 / 60 Hz	EMC	EN61000-6-1/-2/-3/-4
Rated/Max Output AC output		10kVA	
Rated/Max Output Current		14.5A	
Rated/Max Backup Output		10kVA	
Rated/Max Backup Current		14.5A	
AC Output rated voltage		400/380V _{a.c}	
Inverter battery port voltage rating		240~288V _{d.c}	
Operating temperature range		-25~60°C	
Active anti-islanding method		RoCoF	
Inverter Max Efficiency		97.45%	
Country of Manufacture		CHINA	
Grid Regulation		VDE 4105, EN 50549, C10/11, NC RfG, G98, TOR Erzeuger, AS4777.2, PEA, UNE_217002, VDE 0126	

Battery Technical Specification	
Module Model	SMILE-BAT-8.2PH
Module Capacity	8.2 kWh
Usable Capacity	7.8 kWh
Depth of Discharge (DoD)	95%
Nominal Voltage	256 V
Max. Charging/Discharging Current	32 A
Operating Temperature Range	0 °C ~ 49 °C*(Charging mode)/-10~49°C(Discharging mode)
Cycle Life	10000**
Battery Modules Connection	1 ~ 6 in parallel

* Max. charge/discharge current derating will occur related to temperature and SOC.

** Under specific test conditions.

Alpha ESS Australia Pty. Ltd.

☎ +61 02 9000 7676

✉ Australia@alpha-ess.com

🌐 www.alphaess.com

📍 8/15-21 Gibbs Street, Chatswood, NSW 2067 Australia

